

Robust aber kompakt: 3 m Sturzschutz – IP67 – 280 g



- Windows CE® 6.0 R3
- 3 m Sturzschutz und IP67
- 280 g leicht und besonders ergonomisch
- 6,9 cm QVGA-Touchdisplay
- Smart Card Reader / Writer

Spezifikationen		
Modell	DT-X8-10E	DT-X8-20E
CPU	Marvell® PXA320 624MHz	
Betriebssystem	Microsoft® Windows® Embedded CE 6.0 R3 Englische Version	
Strapazierfähigkeit	Sturzschutz	3.0m
	Staub/Spritzwasserschutz	IP67 (Kompatibel mit IEC60529 Standard)
	Betriebs-temperatur	-20°C bis 50°C
Speicher	RAM	128MB
	ROM	256MB (Frei für User: Ca. 160MB)
Display	LCD	Blanview® TFT Farb-LCD mit Touchscreen 5,9 cm (2,7 Inch) QVGA (240x320 Pixel)
	Anzeige	Anzeige 1: Batteriewechsel-Status Anzeige 2: Kabellose Kommunikation und Scan-Status
Eingabe	Tastatur	23 Tasten, inkl. num. Tasten, CLR-Taste, Abschlusstaste, Cursor-Taste, Power-Taste, Trigger-Taste Fn key, F1 zu F8 Taste, L/R-Taste
	Scannertasten	3 (Mitte, Links und rechts)
	Touchscreen	Ja (Resistiver Typ)
Scanner	Typ	Laser-Scanner
	Auflösung	0.127mm
	1D	GS1 DataBar Omnidirectional, GS1 DataBar Truncated, GS1 DataBar Limited, GS1 DataBar Expanded, Code128/GS1-128 (UCC/EAN128), Code93, Code39, EAN8, EAN13, UPC-A, UPC-E, Codabar (NW-7), IATA, MSI, Interleaved 2of5 (ITF), Industrial 2 of 5
	Stacked	GS1 DataBar Stacked, GS1 DataBar Expanded Stacked
		C-MOS Imager
		1D: 0.15mm, Stacked: 0.169mm, Matrix: 0.25mm
		GS1 DataBar Omnidirectional, GS1 DataBar Truncated, GS1 DataBar Limited, GS1 DataBar Expanded, Code128/GS1-128 (UCC/EAN128), Code93, Code39, Code32, Code11, EAN8, EAN13, UPC-A, UPC-E, Codabar (NW-7), IATA, MSI, Interleaved 2 of 5 (ITF)
		GS1 DataBar Stacked, GS1 DataBar Stacked Omnidirectional, GS1 DataBar Expanded Stacked, Code49, PDF417, Micro PDF, Composite, Codablock F, TLC39
		Aztec, DataMatrix, Maxicode, QR Code, microQR
Wireless LAN	Standard	IEEE 802.11b (Maximum: 11Mbps), IEEE 802.11g (Maximum: 54Mbps)
	Sicherheit	WPA2 / AES
Interface	Bluetooth®	Bluetooth® Version 2.0+EDR kompatibel
	Karte	microSD Speicherkarte (SDHC) x 1
	USB Port	Version 1.1 (Host/Client)
	Audio	Mikrofon: integriert (monaural), Lautsprecher: integriert (monaural)
Power	Main Power	Large-capacity lithium-ion battery pack (Operating period: Approx. 20 hours*)
	Memory Backup	Lithium-Batterie (wiederaufladbar) integriert
Vibrator	Standard	
Größe (BxHxT)	Ca. 65,7 (57,4*) x 187,0 x 32,4 (35,0*) mm *Griff außen	
Gewicht	282g (Inklusive großem Akku)	



Windows® and Windows® Embedded are registered trademarks of the Microsoft Corporation, USA. The Bluetooth trademark is owned by Bluetooth SIG, USA and licensed to Casio Computer Co. Ltd. Other product- or company names are

either trademarks or registered trademarks of the respective owners. This publication carries product description without obligation and is not to be seen as a firm offer. Specifications and design are subject to change without notice.

