

C-40

Barcode CCD Scanner

HIGHLIGHTS

- Small form factor
- Integrated decoder
- 300 scans/sec
- Low power consumption



C-40

Basic product specifications

OPERATING INDICATORS

VISUAL: 1 LED (red/green/orange) **NON-VISUAL:** Buzzer

OPERATING KEYS

ENTRY OPTIONS: 1 scan key

COMMUNICATION

USB: Ver. 2.0, HID/COM (VCP)

POWER

VOLTAGE REQUIREMENT: 4.5 - 5.5V

BARCODE SCANNER OPTICS

LIGHT SOURCE: 1 red LED **SCAN METHOD:** CCD linear sensor, 1500 pixels
SCAN RATE: 300 scans/sec **TRIGGER MODE:** Manual, auto-trigger **READING PITCH ANGLE:** -35 to 0°, 0 to +35° **READING SKEW ANGLE:** -30 to 0°, 0 to +70° **READING TILT ANGLE:** -25 to 0°, 0 to +25° **CURVATURE:** R>15 mm (EAN8), R>20 mm (EAN13) **MIN. RESOLUTION AT PCS 0.9:** 0.3 mm **DEPTH OF FIELD:** < 15mm

SUPPORTED SYMBOLOGIES

BARCODE (1D): JAN/UPC/EAN incl. add on, Codabar/NW-7, Code 11, Code 39, Code 93, Code 128, GS1-128 (EAN-128), GS1 DataBar (RSS) (excl. stacked), IATA, Industrial 2of5, Interleaved 2of5, ISBN-ISSN-ISSN, Matrix 2of5, MSI/Plessey, S-Code, Telepen, Tri-Optic, UK/Plessey **POSTAL CODE:** Chinese Post, Korean Postal Authority Code

DURABILITY

TEMPERATURE IN OPERATION: 0 to 50 °C / 32 to 122 °F **TEMPERATURE IN STORAGE:** -20 to 60 °C / -14 to 140 °F **HUMIDITY IN OPERATION:** 5 - 95% (non-condensing) **HUMIDITY IN STORAGE:** 5 - 95% (non-condensing) **AMBIENT LIGHT IMMUNITY:** 10,000 lx **DROP TEST:** 1.5 m / 5 ft drop onto concrete surface **VIBRATION TEST:** 10 - 100 Hz with 2G for 1 hour **PROTECTION RATE:** IP 42

PHYSICAL

DIMENSIONS (W X H X D): 72.7 x 58.3 x 157.7 mm / 2.86 x 2.30 x 6.21 in

WEIGHT BODY: Ca. 73 g / 2,57 oz (excl. cable) **CASE:** PC & ABS, white

REGULATORY & SAFETY

PRODUCT COMPLIANCE: CE, FCC, VCCI, RoHS, IEC62471, EN61000

